



## #10168 1-1/2" x 1/2" x 1/4"-20 Threaded Mounted Flap Wheel

Quick change threaded mandrel provides fast changeover between worn and new wheels, or between sizes and grits. Flaps wear evenly exposing fresh cuts throughout life. Used with a threaded mandrel adapter, no extra tooling is necessary.

## **Specifications**

Diameter	1-1/2"
Width	1/2"
Shank Diameter	1/4"-20
Max RPM	23,000
Opt RPM	9,600
Brand	SHUR-KUT™
Material Type	Coated
Abrasive Grain	Aluminum Oxide
Color Family	Brown
Backing Type	Cloth
Backing Material	Cotton
Backing Weight	X-Wt.
Bond Type	Resin/Resin
Grain Coverage	Closed Coat
Mounting	Shank Mounted
Product Form	Flap Wheel
Grit	80
Standard Package Quantity	10
Stock Status	Stock

## Features / Applications

Flexible flaps are arranged radially around a center core allowing high removal and finishing rates with reduced pressure and fatigue from operators. The flexibility of the flaps allows excellent control and conformability on contours and inside or around intricate parts. As the grains wear away, so does the cloth backing, continually exposing fresh abrasive material and sharp cutting grains. The variety of shapes and sizes available provide versatility in grinding, deburring and polishing flat or contoured surfaces and edges. Several mounting options are available for many tools, including right angle grinders.

Features	Contoured grinding and finishing Inner tube deburring, cleaning
	and polishing
	Shaping or refining contours on
	cast or machined parts
	Weld seam blending or finishing

## **Additional Information**

**Proposition 65 Warning Statement** WARNING: Cancer - www.P65Warnings.ca.gov