



## #10185 2" x 1" x 1/4"-20 Threaded Mounted Flap Wheel

Quick change threaded mandrel provides fast changeover between worn and new wheels, or between sizes and grits. Flaps wear evenly exposing fresh cuts throughout life. Used with a threaded mandrel adapter, no extra tooling is necessary.

### Specifications

<b>Diameter</b>	2"
<b>Width</b>	1"
<b>Shank Diameter</b>	1/4"-20
<b>Max RPM</b>	23,000
<b>Opt RPM</b>	7,000
<b>Brand</b>	SHUR-KUT™
<b>Material Type</b>	Coated
<b>Abrasive Grain</b>	Aluminum Oxide
<b>Color Family</b>	Brown
<b>Backing Type</b>	Cloth
<b>Backing Material</b>	Cotton
<b>Backing Weight</b>	X-Wt.
<b>Bond Type</b>	Resin/Resin
<b>Grain Coverage</b>	Closed Coat
<b>Mounting</b>	Shank Mounted
<b>Product Form</b>	Flap Wheel
<b>Grit</b>	80
<b>Standard Package Quantity</b>	10
<b>Stock Status</b>	Stock

### Features / Applications

Flexible flaps are arranged radially around a center core allowing high removal and finishing rates with reduced pressure and fatigue from operators. The flexibility of the flaps allows excellent control and conformability on contours and inside or around intricate parts. As the grains wear away, so does the cloth backing, continually exposing fresh abrasive material and sharp cutting grains. The variety of shapes and sizes available provide versatility in grinding, deburring and polishing flat or contoured surfaces and edges. Several mounting options are available for many tools, including right angle grinders.

### Features

Contoured grinding and finishing  
Inner tube deburring, cleaning  
and polishing  
Shaping or refining contours on  
cast or machined parts  
Weld seam blending or finishing

### Additional Information

#### Proposition 65 Warning Statement

WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)