

**#10430**
6" x 2" x 1" Unmounted Duplex Wheel

Conformable, yet sturdy action for stationary equipment and smaller, hand-held parts. Easily remove surface coatings or oxidation, blend or repair finishes on which slight material removal may be necessary.

Specifications

Diameter	6"
Width	2"
Arbor Diameter	1"
Max RPM	3,400
Opt RPM	2,000
Brand	SHUR-BRITE™
Material Type	Nonwoven
Nonwoven Class	Heavy Duty
Nonwoven Category	Satin Finishing
Abrasive Grain	Aluminum Oxide
Color Family	Maroon
Backing Weight	X-Wt.
Mounting	Unmounted
Product Form	Duplex Wheel
Grit	120
Grade	VFN
Standard Package Quantity	5
Stock Status	Stock

Features / Applications

Simultaneous cutting action from alternating coated and satin flaps for controlled balance of aggressive finishing and cushioned finesse. Conforms to slight contours and less intricate parts while still able to shape and remove material.

Features

Coated flaps remove and clean surface imperfections
Satin flaps blend and finish parts
Remove & blend parting lines or small welds in one operation
Blend or repair scratch patterns

Additional Information

Proposition 65 Warning Statement

WARNING: Cancer and Reproductive Harm -
www.P65Warnings.ca.gov
