

**#10459**  
**2-3/8" x 1" x 1/4" Disc Wheel**

Due to the material profile running parallel to the workpiece, Mounted Disc Wheels are less aggressive than Flap Brushes, but produce a consistent satin finish. Disc Wheels are conformable and will not alter part geometry, ideal for removing light surface coatings or contaminants.

**Specifications**

<b>Diameter</b>	2-3/8"
<b>Width</b>	1"
<b>Shank Diameter</b>	1/4"
<b>Max RPM</b>	12,000
<b>Opt RPM</b>	5,000
<b>Brand</b>	SHUR-BRITE™
<b>Material Type</b>	Nonwoven
<b>Nonwoven Class</b>	High Strength
<b>Nonwoven Category</b>	Satin Finishing
<b>Abrasive Grain</b>	Aluminum Oxide
<b>Color Family</b>	Maroon
<b>Waterproof</b>	Yes
<b>Mounting</b>	Shank Mounted
<b>Product Form</b>	Disc Wheel
<b>Grade</b>	MED
<b>Standard Package Quantity</b>	5
<b>Stock Status</b>	Stock

**Features / Applications**

Due to the material profile running parallel to the workpiece, Mounted Disc Wheels are less aggressive than Flap Brushes, but produce a consistent satin finish. Disc Wheels are conformable and will not alter part geometry, ideal for removing light surface coatings or contaminants.

**Features**

Conformable to contours and intricate parts  
Will not alter workpiece tolerances  
Portable, cushioned finishing and surface prep  
Also available in Heavy Duty grades

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)