

**#10583B**  
**5" Hook & Loop Disc**

Controlled cut rate and surface finishing range on harder metals. Balanced density of grains and resin reduce heat generation, loading and smearing on both hard or soft materials.

**Specifications**

<b>Diameter</b>	5"
<b>Max RPM</b>	7,000
<b>Opt RPM</b>	2,600
<b>Brand</b>	SHUR-BRITE™
<b>Material Type</b>	Nonwoven
<b>Nonwoven Class</b>	Grind Duty
<b>Nonwoven Category</b>	Surface Conditioning
<b>Abrasive Grain</b>	Aluminum Oxide
<b>Color Family</b>	Brown/Brown
<b>Backing Type</b>	Scrim
<b>Waterproof</b>	Yes
<b>Attachment Type</b>	Hook & Loop
<b>Product Form</b>	Hook & Loop Disc
<b>Grade</b>	CRS
<b>Standard Package Quantity</b>	20
<b>Stock Status</b>	Stock

**Features / Applications**

For removal, blending, surface preparation and finishing of larger areas, the hook and loop attachment system safely secures larger diameter discs to multiple tools. Compared to smaller quick change discs, full surface treatments of larger workpieces can be completed with less changeover, and product or operator fatigue. Best for flat and moderately contoured surfaces, materials available are well suited for a variety of industrial applications.

**Features**

Blending or refining scratch patterns  
Moderate cushion and flexibility  
Reduced risk of gouging soft materials  
Consistent performance  
Several grades available for progressive finishing

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)