

**#10623**  
**3-1/2" x 15-1/2" Flex Belt**

A variety of sizes available for use with small contact wheels to access intricate areas. Exceptional flexibility and edge durability for detail work over contours and corners.

**Specifications**

<b>Width</b>	3-1/2"
<b>Length</b>	15-1/2"
<b>Brand</b>	SHUR-BRITE™
<b>Material Type</b>	Nonwoven
<b>Nonwoven Class</b>	Flex
<b>Nonwoven Category</b>	Surface Conditioning
<b>Abrasive Grain</b>	Aluminum Oxide
<b>Color Family</b>	Maroon/Green
<b>Backing Type</b>	Flex
<b>Waterproof</b>	Yes
<b>Product Form</b>	Belt
<b>Grade</b>	MED
<b>Standard Package Quantity</b>	10
<b>Stock Status</b>	Stock

**Features / Applications**

The open structure of surface conditioning belts resists overheating, part discoloration or loading, ensuring consistent quality throughout life - important factors when decorating or finishing large surface areas. In narrow or short form, like file belts, the surface conditioning material is manufactured with additional flex, easily conforming to small contact wheels and narrow areas of the workpiece. Wide belts utilize a low stretch reinforcement, providing stability and reduced changeover on large, robotic equipment.

**Features**

Thin, pliable reinforcement  
Flexible over small contact wheels  
Conforms to smaller areas

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)