

**#11722**  
**4-1/2" x 7/8" Resin Fiber Disc**

Tough, blocky grain well suited for general purpose grinding and stock removal. Rigid pressure cuts faster. Durable use on ferrous, non-ferrous, stainless steels, alloys and non-metallics.

**Specifications**

<b>Diameter</b>	4-1/2"
<b>Arbor Diameter</b>	7/8"
<b>Max RPM</b>	13,300
<b>Opt RPM</b>	8,000
<b>Brand</b>	SHUR-KUT™
<b>Material Type</b>	Coated
<b>Abrasive Grain</b>	Aluminum Oxide
<b>Product Form</b>	Resin Fiber Disc
<b>Grit</b>	80
<b>Standard Package Quantity</b>	25
<b>Stock Status</b>	Stock

**Features / Applications**

A dense, rigid backing is utilized for better grain retention and direct pressure from abrasive grains, creating a heavy duty, aggressive cutting action. Best for flat surfaces with minimal contours, resin fiber discs can provide the most aggressive and heavy stock removal of all coated abrasives. The substantial surface area minimizes time taken to finish large areas. Used with an air-cooled backing pad, heat is dissipated to reduce overheating and loading, providing a long life from resin fiber discs.

<b>Features</b>	General stock removal and shaping Weld removal and blending Leveling or blending imperfections
-----------------	--

**Additional Information****Proposition 65 Warning Statement**WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)