

**#11726****5" x 7/8" Resin Fiber Disc**

Tough, blocky grain well suited for general purpose grinding and stock removal. Rigid pressure cuts faster. Durable use on ferrous, non-ferrous, stainless steels, alloys and non-metallics.

Specifications

Diameter	5"
Arbor Diameter	7/8"
Max RPM	13,000
Opt RPM	7,000
Brand	SHUR-KUT™
Material Type	Coated
Abrasive Grain	Aluminum Oxide
Color Family	Maroon
Backing Type	Fiber
Bond Type	Resin/Resin
Grain Coverage	Closed Coat
Product Form	Resin Fiber Disc
Grit	24
Standard Package Quantity	25
Stock Status	Stock

Features / Applications

A dense, rigid backing is utilized for better grain retention and direct pressure from abrasive grains, creating a heavy duty, aggressive cutting action. Best for flat surfaces with minimal contours, resin fiber discs can provide the most aggressive and heavy stock removal of all coated abrasives. The substantial surface area minimizes time taken to finish large areas. Used with an air-cooled backing pad, heat is dissipated to reduce overheating and loading, providing a long life from resin fiber discs.

Features

General stock removal and shaping
Weld removal and blending
Leveling or blending imperfections

Additional Information**Proposition 65 Warning Statement**

WARNING: Cancer - www.P65Warnings.ca.gov