

**#11748****4-1/2" x 7/8" Resin Fiber Disc**

Dense grains continually generate new cutting edges, ideal for long lasting stock removal. Rigid backing provides additional pressure for sharp grains to break down properly.

**Specifications**

|                                  |                  |
|----------------------------------|------------------|
| <b>Diameter</b>                  | 4-1/2"           |
| <b>Arbor Diameter</b>            | 7/8"             |
| <b>Max RPM</b>                   | 13,300           |
| <b>Opt RPM</b>                   | 8,000            |
| <b>Brand</b>                     | SHUR-KUT™        |
| <b>Material Type</b>             | Coated           |
| <b>Abrasive Grain</b>            | Zirconia         |
| <b>Product Form</b>              | Resin Fiber Disc |
| <b>Grit</b>                      | 24               |
| <b>Standard Package Quantity</b> | 25               |
| <b>Stock Status</b>              | Non-Stock        |

**Features / Applications**

A dense, rigid backing is utilized for better grain retention and direct pressure from abrasive grains, creating a heavy duty, aggressive cutting action. Best for flat surfaces with minimal contours, resin fiber discs can provide the most aggressive and heavy stock removal of all coated abrasives. The substantial surface area minimizes time taken to finish large areas. Used with an air-cooled backing pad, heat is dissipated to reduce overheating and loading, providing a long life from resin fiber discs.

**Features**

Aggressive stock removal on hard metals and alloys  
Sharp cut reduces heat, friction and loading  
High pressure applications

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)