

**#11974**  
**3/4" x 2" Spiral Band**

General purpose cutting action and durable use on ferrous, non-ferrous, stainless steel, alloys and non-metallics. Rigid design quickly removes stock and is precise in diameter grinding.

**Specifications**

|                                  |                |
|----------------------------------|----------------|
| <b>Diameter</b>                  | 3/4"           |
| <b>Length</b>                    | 2"             |
| <b>Max RPM</b>                   | 9,000          |
| <b>Brand</b>                     | SHUR-KUT™      |
| <b>Material Type</b>             | Coated         |
| <b>Abrasive Grain</b>            | Aluminum Oxide |
| <b>Color Family</b>              | Brown          |
| <b>Backing Type</b>              | Cloth          |
| <b>Backing Material</b>          | Cotton         |
| <b>Backing Weight</b>            | X-Wt.          |
| <b>Bond Type</b>                 | Resin/Resin    |
| <b>Grain Coverage</b>            | Closed Coat    |
| <b>Product Form</b>              | Spiral Band    |
| <b>Grit</b>                      | 36             |
| <b>Standard Package Quantity</b> | 100            |
| <b>Stock Status</b>              | Non-Stock      |

**Features / Applications**

The solid, single layer design of spiral bands produces rapid material removal on curved or contoured parts. Used with a well-balanced rubber drum, bands are smooth in operation and do not chatter during use. With the firm combination of abrasive band and rubber drum, precise diameter grinding and finishing is achievable.

**Features**

Remove or shape parts quickly  
Navigate contoured surfaces easily  
Fast changeover with no tooling  
Parting line and flash removal  
Precise deburring and blending

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)