

**#21950****4-1/2" x 7/8" Type 29 HD Flap Disc**

Added layers of dense grains well suited for general purpose grinding and stock removal. Durable use on ferrous, non-ferrous, stainless steels, alloys and non-metallics. Ideal for mild steels and aluminum.

Specifications

Diameter	4-1/2"
Arbor Diameter	7/8"
Type	Type 29
Shape	Angle
Density	High
Max RPM	13,300
Brand	SHUR-KUT™
Material Type	Coated
Abrasive Grain	Aluminum Oxide
Color Family	Maroon
Backing Type	Cloth
Backing Material	Poly/Cotton; Cotton
Backing Weight	X-Wt.
Bond Type	Resin/Resin
Grain Coverage	Closed Coat
Product Form	Flap Disc
Grit	40
Standard Package Quantity	10
Stock Status	Stock

Features / Applications

Overlapping layers of coated abrasives wear down to expose new cutting surfaces, allowing extended use of flap discs and much more control and comfort than rigid grinding wheels. The profile of flap discs, either flat faced (Type 27) or angle faced (Type 29) controls the amount of leverage applied to surfaces. Type 27 flap discs are better for finesse and extended use, whereas Type 29 discs are much more aggressive. Standard density discs provide less flap compression, best suited for stock removal and rough shaping. High density discs utilize more flaps, prolonging life, and are less compressed, allowing limited conformability to the workpiece.

Features

General stock removal and shaping on most metals
Increased flap count extends life
Blending and beveling

Additional Information**Proposition 65 Warning Statement**

WARNING: Cancer - www.P65Warnings.ca.gov