

**#26304****6" x 2" x 1" Unmounted Flap Wheel**

Spindle mounted wheels used with stationary equipment or adaptable handheld tools. Shape, finish and polish handheld parts, or produce linear finishes on flat parts. Longer, more flexible flaps finesse and conform to contours and smaller parts.

Specifications

Diameter	6"
Width	2"
Arbor Diameter	1"
Max RPM	5,700
Opt RPM	5,000
Brand	SHUR-KUT™
Material Type	Coated
Abrasive Grain	Aluminum Oxide
Color Family	Brown
Backing Type	Cloth
Backing Material	Cotton
Backing Weight	X-Wt.
Bond Type	Resin/Resin
Grain Coverage	Closed Coat
Mounting	Unmounted
Product Form	Flap Wheel
Grit	40
Standard Package Quantity	5
Stock Status	Stock

Features / Applications

Flexible flaps are arranged radially around a center core allowing high removal and finishing rates with reduced pressure and fatigue from operators. The flexibility of the flaps allows excellent control and conformability on contours and inside or around intricate parts. As the grains wear away, so does the cloth backing, continually exposing fresh abrasive material and sharp cutting grains. The variety of shapes and sizes available provide versatility in grinding, deburring and polishing flat or contoured surfaces and edges. Several mounting options are available for many tools, including right angle grinders.

Features

Contoured grinding and finishing
Shaping or refining contours on cast or machined parts
Weld seam blending or finishing
Straight line finishing and surface preparation

Additional Information**Proposition 65 Warning Statement**WARNING: Cancer - www.P65Warnings.ca.gov