



#27147B 5" x 7/8" Hook & Loop Disc

An assisted-centering arbor hole ensures consistent disc alignment every changeover. Use on right angle grinders with rubber backing pad and retainer nut, for higher rotational speed.

Controlled cut rate and surface finishing range on harder metals. Balanced density of grains and resin reduce heat generation, loading and smearing on both hard or soft materials.

Specifications

| Diameter | 5" |
|------------------------------|----------------------|
| Arbor Diameter | 7/8" |
| Max RPM | 7,000 |
| Opt RPM | 2,600 |
| Brand | SHUR-BRITE™ |
| Material Type | Nonwoven |
| Nonwoven Class | Grind Duty |
| Nonwoven Category | Surface Conditioning |
| Abrasive Grain | Aluminum Oxide |
| Color Family | Brown/Brown |
| Backing Type | Scrim |
| Waterproof | Yes |
| Attachment Type | Hook & Loop |
| Mounting | Arbor Mounted |
| Product Form | Hook & Loop Disc |
| Grade | CRS |
| Standard Package Quantity | 20 |
| | |
| Stock Status | Stock |

Features / Applications

For removal, blending, surface preparation and finishing of larger areas, the hook and loop attachment system safely secures larger diameter discs to multiple tools. Compared to smaller quick change discs, full surface treatments of larger workpieces can be completed with less changeover, and product or operator fatigue. Best for flat and moderately contoured surfaces, materials available are well suited for a variety of industrial applications.

| Features | Blending or refining scratch |
|----------|----------------------------------|
| | patterns |
| | Moderate cushion and flexibility |
| | Reduced risk of gouging soft |
| | materials |
| | Consistent performance |

Additional Information

Proposition 65 Warning Statement

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov