



#37864 2" Type R Mini Flex Disc

Compressible flaps extend outward to conform and reach small areas and run against inside corners. Durable use on ferrous, non-ferrous, stainless steels, alloys and non-metallics. Ideal for mild steels and aluminum.

Specifications

Diameter	2"
Button Type	Type R
Max RPM	25,000
Opt RPM	13,000
Brand	SHUR-KUT™
Material Type	Coated
Abrasive Grain	Aluminum Oxide
Color Family	Maroon
Backing Type	Fiber
Bond Type	Resin/Resin
Grain Coverage	Closed Coat
Product Form	Flap Disc
Grit	120
Standard Package Quantity	10
Stock Status	Non-Stock

Additional Information

Proposition 65 Warning Statement

WARNING: Cancer - www.P65Warnings.ca.gov

Features / Applications

Overlapping layers of coated abrasives wear down to expose new cutting surfaces, allowing extended use of flap discs and much more control and comfort than rigid grinding wheels. The profile of flap discs, either flat faced (Type 27) or angle faced (Type 29) controls the amount of leverage applied to surfaces. Type 27 flap discs are better for finesse and extended use, whereas Type 29 discs are much more aggressive. Standard density discs provide less flap compression, best suited for stock removal and rough shaping. High density discs utilize more flaps, prolonging life, and are less compressed, allowing limited conformability to the workpiece.

Features

General purpose grinding and blending
Flap overhang reaches small areas
Conformable and controllable
Quick change functionality for die grinders