

**#37898**  
**2" Type R Mini Flap Disc**

Small footprint for aggressive grinding and stock removal in smaller areas. Overlapping flaps wear away to fresh cutting surfaces, prolonging disc life and use. Quick change functionality alleviates production downtime.

**Specifications**

|                                  |           |
|----------------------------------|-----------|
| <b>Diameter</b>                  | 2"        |
| <b>Button Type</b>               | Type R    |
| <b>Max RPM</b>                   | 25,000    |
| <b>Opt RPM</b>                   | 13,000    |
| <b>Brand</b>                     | SHUR-KUT™ |
| <b>Material Type</b>             | Coated    |
| <b>Abrasive Grain</b>            | Zirconia  |
| <b>Product Form</b>              | Flap Disc |
| <b>Grit</b>                      | 80        |
| <b>Standard Package Quantity</b> | 10        |
| <b>Stock Status</b>              | Stock     |

**Features / Applications**

Overlapping layers of coated abrasives wear down to expose new cutting surfaces, allowing extended use of flap discs and much more control and comfort than rigid grinding wheels. The profile of flap discs, either flat faced (Type 27) or angle faced (Type 29) controls the amount of leverage applied to surfaces. Type 27 flap discs are better for finesse and extended use, whereas Type 29 discs are much more aggressive. Standard density discs provide less flap compression, best suited for stock removal and rough shaping. High density discs utilize more flaps, prolonging life, and are less compressed, allowing limited conformability to the workpiece.

**Features**

Aggressive removal in small areas  
Quick changeover between discs  
Sharp cuts reduce heat and loading  
High pressure applications

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)