



#46860 3" Type S RIGID-KUT Quick Change Disc

Stiff backing keeps grains in place during aggressive, general purpose applications. High edge retention resists shredding during sharp deburring applications. Dense aluminum oxide grains suitable for most metals and general applications.

Specifications

| | |
|----------------------------------|----------------------|
| Diameter | 3" |
| Button Type | Type S |
| Max RPM | 20,000 |
| Opt RPM | 7,000 |
| Brand | SHUR-KUT™ RIGID-KUT™ |
| Sub-Brand | RIGID-KUT™ |
| Material Type | Coated |
| Abrasive Grain | Aluminum Oxide |
| Color Family | Maroon |
| Backing Type | Cloth |
| Backing Material | Cotton |
| Backing Weight | X-Wt. |
| Bond Type | Resin/Resin |
| Grain Coverage | Closed Coat |
| Product Form | Quick Change Disc |
| Grit | 50 |
| Standard Package Quantity | 50 |
| Stock Status | Non-Stock |

Features / Applications

The reduced diameter of quick change discs provide ease of use on intricate parts, and excellent control when shaping or blending surface portions. Ideally used on flat surfaces to utilize more cutting action, the moderate flexibility of quick change discs and their holders also allow contouring and access to inner corners. The unique quick change functionality reduces changeover downtime and eases transitions between grit, material, or even abrasive type where multistep processes are required.

| | |
|-----------------|--|
| Features | Dense grains ideal for stock removal Highly resistant to shredding Heavy deburring and edge applications |
|-----------------|--|

Additional Information

Proposition 65 Warning Statement

WARNING: Cancer - www.P65Warnings.ca.gov