

**#52401**  
**3/4" x 3/4" x 1/4" Mounted Duplex Wheel**

Tough but conformable wheels able to reach smaller areas and inner diameters and contours. Ideal for consolidating removal and blending steps into one operation.

**Specifications**

<b>Diameter</b>	3/4"
<b>Width</b>	3/4"
<b>Shank Diameter</b>	1/4"
<b>Max RPM</b>	15,000
<b>Opt RPM</b>	10,500
<b>Brand</b>	SHUR-BRITE™
<b>Material Type</b>	Nonwoven
<b>Nonwoven Class</b>	Heavy Duty
<b>Nonwoven Category</b>	Satin Finishing
<b>Abrasive Grain</b>	Aluminum Oxide
<b>Mounting</b>	Shank Mounted
<b>Product Form</b>	Duplex Wheel
<b>Grit</b>	180
<b>Standard Package Quantity</b>	5
<b>Stock Status</b>	Non-Stock

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**Features / Applications**

Simultaneous cutting action from alternating coated and satin flaps for controlled balance of aggressive finishing and cushioned finesse. Conforms to slight contours and less intricate parts while still able to shape and remove material.

**Features**

Coated flaps remove and clean surface imperfections  
Satin flaps blend and finish parts  
Easily remove and blend seams, parting lines or small welds in one operation  
Blend or repair flat or contoured scratch patterns