

**#53876****2" Type R Quick Change Disc**

The finer crystalline structure of Ceramic Advantage grains enhances self-sharpening effects, resulting in consistent performance throughout life. The increased amount of smaller cutting points provides a finer finish and longer life under moderate pressure.

**Specifications**

|                                  |                   |
|----------------------------------|-------------------|
| <b>Diameter</b>                  | 2"                |
| <b>Button Type</b>               | Type R            |
| <b>Max RPM</b>                   | 30,000            |
| <b>Opt RPM</b>                   | 10,500            |
| <b>Brand</b>                     | SHUR-KUT™         |
| <b>Material Type</b>             | Coated            |
| <b>Abrasive Grain</b>            | Ceramic           |
| <b>Grain Enhancement</b>         | Advantage         |
| <b>Grinding Aid</b>              | Yes               |
| <b>Color Family</b>              | Maroon            |
| <b>Backing Type</b>              | Cloth             |
| <b>Backing Material</b>          | Polyester         |
| <b>Backing Weight</b>            | Y-Wt.             |
| <b>Bond Type</b>                 | Resin/Resin       |
| <b>Grain Coverage</b>            | Semi-Closed Coat  |
| <b>Waterproof</b>                | Yes               |
| <b>Product Form</b>              | Quick Change Disc |
| <b>Grit</b>                      | 120               |
| <b>Standard Package Quantity</b> | 100               |
| <b>Stock Status</b>              | Stock             |

**Features / Applications**

The reduced diameter of quick change discs provide ease of use on intricate parts, and excellent control when shaping or blending surface portions. Ideally used on flat surfaces to utilize more cutting action, the moderate flexibility of quick change discs and their holders also allow contouring and access to inner corners. The unique quick change functionality reduces changeover downtime and eases transitions between grit, material, or even abrasive type where multistep processes are required.

|                     |                                                                                                                                                                                                                     |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Features</b>     | Medium operator pressure<br>Continual exposure of fresh, sharp cutting points<br>Top size coat reduces loading, glazing and dulling                                                                                 |
| <b>Applications</b> | General purpose grinding and stock removal<br>Deburring or parting line removal on cast parts<br>Spot weld removal and blending<br>Mold and cavity grinding and refurbishing<br>Grinding and preparing hot castings |

**Additional Information****Proposition 65 Warning Statement**WARNING: Cancer - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)