

**#54654****1" x 1/8" x 1/8" Unitized Wheel**

Conforming structure cuts consistently throughout wheel life without heat buildup, extending life on soft and exotic alloys. Nonwoven structure will not disrupt critical part tolerances while cleaning or removing residue, finishing or polishing.

Specifications

Diameter	1"
Thickness	1/8"
Arbor Diameter	1/8"
Max RPM	35,100
Opt RPM	10,500
Brand	SHUR-BRITE™
Material Type	Nonwoven
Nonwoven Category	Unitized
Abrasive Grain	Aluminum Oxide
Mounting	Arbor Mounted
Product Form	Arbor Mounted Wheel
Grade	8AC
Standard Package Quantity	10
Stock Status	Stock

Features / Applications

The layered, non-directional construction of SHUR-BRITE™ Unitized Wheels and Discs ensures continual exposure of abrasive grains during surface preparation, cleaning, blending and polishing operations. A variety of sizes and grades are available for use with intricate components to larger workpieces. Due to the conforming nature of unitized materials, surface requirements can be achieved without affecting workpiece tolerances, and with minimal heat buildup.

Features

Consistent cut life and heat tolerance
Finish turbine blades and aerospace parts
Remove machining marks or process traces

Additional Information

Proposition 65 Warning Statement	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
---	---