

**#54668**  
**3" x 1/4" x 1/4" Unitized Wheel**

Conforming structure cuts consistently throughout wheel life without heat buildup, extending life on soft and exotic alloys. Nonwoven structure will not disrupt critical part tolerances while cleaning or removing residue, finishing or polishing.

**Specifications**

<b>Diameter</b>	3"
<b>Thickness</b>	1/4"
<b>Arbor Diameter</b>	1/4"
<b>Max RPM</b>	15,100
<b>Opt RPM</b>	6,400
<b>Brand</b>	SHUR-BRITE™
<b>Material Type</b>	Nonwoven
<b>Nonwoven Category</b>	Unitized
<b>Abrasive Grain</b>	Aluminum Oxide
<b>Mounting</b>	Arbor Mounted
<b>Product Form</b>	Arbor Mounted Wheel
<b>Grade</b>	2AM
<b>Standard Package Quantity</b>	10
<b>Stock Status</b>	Stock

**Features / Applications**

The layered, non-directional construction of SHUR-BRITE™ Unitized Wheels and Discs ensures continual exposure of abrasive grains during surface preparation, cleaning, blending and polishing operations. A variety of sizes and grades are available for use with intricate components to larger workpieces. Due to the conforming nature of unitized materials, surface requirements can be achieved without affecting workpiece tolerances, and with minimal heat buildup.

**Features**

Consistent cut life and heat tolerance  
Finish turbine blades and aerospace parts  
Remove machining marks or process traces

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)