

**#54725****3" x 1/4" x 1/4" Unitized Wheel**

Reach small and intricate areas to safely deburr, clean or polish without damaging parts. Compressed nonwoven material will conform to contours and acute angles and not alter part geometry.

Specifications

Diameter	3"
Thickness	1/4"
Shank Diameter	1/4"
Max RPM	18,100
Opt RPM	6,400
Brand	SHUR-BRITE™
Material Type	Nonwoven
Nonwoven Category	Unitized
Abrasive Grain	Aluminum Oxide
Mounting	Shank Mounted
Product Form	Shank Mounted Wheel
Grade	6AM
Standard Package Quantity	10
Stock Status	Non-Stock

Features / Applications

The layered, non-directional construction of SHUR-BRITE™ Unitized Wheels and Discs ensures continual exposure of abrasive grains during surface preparation, cleaning, blending and polishing operations. A variety of sizes and grades are available for use with intricate components to larger workpieces. Due to the conforming nature of unitized materials, surface requirements can be achieved without affecting workpiece tolerances, and with minimal heat buildup.

Features

Easily navigate intricate parts
Light deburring in narrow areas
Clean or finish small, TIG welded parts or seams
No mandrels or adapters required

Additional Information**Proposition 65 Warning Statement**

WARNING: Cancer and Reproductive Harm -
www.P65Warnings.ca.gov