



Specifications

Diameter	3"
Thickness	1/4"
Shank Diameter	1/4"
Max RPM	18,100
Opt RPM	6,400
Brand	SHUR-BRITE™
Material Type	Nonwoven
Nonwoven Category	Unitized
Abrasive Grain	Silicon Carbide
Mounting	Shank Mounted
Product Form	Shank Mounted Wheel
Grade	4SF
Standard Package Quantity	10
Stock Status	Stock

Additional Information

Proposition 65 Warning Statement

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

#54829

3" x 1/4" x 1/4" Unitized Wheel

Reach small and intricate areas to safely deburr, clean or polish without damaging parts. Compressed nonwoven material will conform to contours and acute angles and not alter part geometry.

Features / Applications

The layered, non-directional construction of SHUR-BRITE™ Unitized Wheels and Discs ensures continual exposure of abrasive grains during surface preparation, cleaning, blending and polishing operations. A variety of sizes and grades are available for use with intricate components to larger workpieces. Due to the conforming nature of unitized materials, surface requirements can be achieved without affecting workpiece tolerances, and with minimal heat buildup.

Features	Easily navigate intricate parts Light deburring in narrow areas Clean or finish small, TIG welded parts or seams No mandrels or adapters required
-----------------	--