

**#54898****6" x 1/2" x 1/2" Stripping Wheel**

Aggressive removal of surface layers and contaminants. Extended wheel life and consistent cutting action. Can be stacked on stationary spindles to increase surface coverage and removal rate.

**Specifications**

|                                  |                     |
|----------------------------------|---------------------|
| <b>Diameter</b>                  | 6"                  |
| <b>Width</b>                     | 1/2"                |
| <b>Arbor Diameter</b>            | 1/2"                |
| <b>Max RPM</b>                   | 5,500               |
| <b>Opt RPM</b>                   | 3,000               |
| <b>Brand</b>                     | SHUR-BRITE™         |
| <b>Material Type</b>             | Nonwoven            |
| <b>Nonwoven Class</b>            | Red                 |
| <b>Nonwoven Category</b>         | Stripping           |
| <b>Grain Enhancement</b>         | Red                 |
| <b>Mounting</b>                  | Arbor Mounted       |
| <b>Product Form</b>              | Arbor Mounted Wheel |
| <b>Grade</b>                     | XCRS                |
| <b>Standard Package Quantity</b> | 10                  |
| <b>Stock Status</b>              | Stock               |

**Features / Applications**

Stripping products are aggressive enough to quickly remove layers of paint, residue, corrosion or rust, but the flexibility will not alter or reshape the solid surface underneath. The open, nonwoven structure resists heat buildup, which could cause excessive loading of some surface layers. Stripping products can be used on all sides and offer consistent performance throughout life.

**Features**

Anti-clogging structure  
Quickly remove powder coatings  
Consistent, extended cutting action

**Additional Information****Proposition 65 Warning Statement**

WARNING: Cancer and Reproductive Harm -  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)