SHUR-BRITE® Satin Finishing

Satin Finishing Discs

Due to the high strength nylon fibers and resin content, satin finishing discs can withstand higher rotational speed in both stationary or portable use, for flat or on-edge application. Both quick change and arbor mounted options are available for use with small or intricate parts to larger contours.

Features

- Easily conforms to acute or inaccessible areas
- Cushion and control for critical tolerance and finesse
- Protection from gouging or marring workpieces
- Varying grades and densities for a wide range of applications

HIGH STRENGTH SATIN QUICK CHANGE DISCS

Durable and long-lasting finishing when a higher cut rate is necessary. Strong fibers resist snagging or tearing on intricate parts and can handle higher applied pressure. The quick change holder provides directional pressure from the tool for better control and off-hand finesse.

- ▶ Edge deburring on extrusions
- Finishing brass or steel stampings
- Final finishing of intricate aerospace parts

Туре	Diameter	Max RPM	Optimal RPM	Std. Pkg.	MED	FINE	VFN
Type S	2"	12,000	7,000	50	46588	46589	46590
	3″	8,000	4,500	25	46591	46592	46593
Type R	2"	12,000	7,000	50	38857	38858	38859
	3″	8,000	4,500	25	38860	38861	38862

Ferrous

Non-Ferrous

Stainless

Exotic Alloys

Plastics

Composites

SUPERIOR ABRASIVES, LLC. (800) 235-9123



HEAVY DUTY SATIN QUICK CHANGE DISCS

Less dense and aggressive than HS quick change discs, finer grades are reinforced with a cloth backing. For light cleaning or finishing, suitable for soft materials.

- Decorative blending or finishing
- Oxidation removal from small areas
- Micro-deburring or seam cleaning
- From matte finish to low polish



Туре	Diameter	Max RPM	Optimal RPM	Std. Pkg.	CRS	MED	FINE	VFN
Type S	2"	12,000	7,000	50	10511	10512	10513	10514
	3″	8,000	4,500	25	10515	10516	10517	10518
Type R	2"	12,000	7,000	50	38213	40170	46649	38214
	3″	8,000	4,500	25	40508	39911	46585	39931
		_		_				

Ferrous

Non-Ferrous

Stainless

Exotic Alloys

Plastics

Composites



QUICK CHANGE DISC HOLDERS

Туре	Diameter	Shank	Max RPM	Std. Pkg.	Part #
Type S	2"	1/4"	30,000	1	11173
	3"	1/4"	20,000	1	11176
Type R	2"	1/4″	30,000	1	11275
	3"	1/4″	20,000	1	11276

