SHUR-KUT® Coated

Spiral Bands

The solid, single layer design of spiral bands produces rapid material removal on curved or contoured parts. Used with a well-balanced rubber drum, bands are smooth in operation and do not chatter during use. With the firm combination of abrasive band and rubber drum, precise diameter grinding and finishing is achievable.

Applications

- Fast and aggressive blending and removal
- Remove flash or burrs from small parts
- Precision diameter grinding
- Cast parting line removal





General purpose cutting action and durable use on ferrous, non-ferrous, stainless steel, alloys and non-metallics. Rigid design quickly removes stock and is precise in diameter grinding.

- Remove or shape parts quickly
- Navigate contoured surfaces easily
- Fast changeover with no tooling
- Parting line and flash removal
- Precise deburring and blending





Diameter	Length	Max RPM	Std. Pkg.	36	60	80	120
1/2″	1/2″	30,000	100	52306	11947	11948	11949
1/2"	1″	20,000	100	11950	11953	11954	11955
3/4"	3/4"	24,000	100	-	18101	18882	19297
3/4"	1″	19,000	100	11962	11965	11966	11967
3/4"	2"	9,000	100	11974	11977	11978	19321
1"	1″	15,000	100	11981	11984	11985	11986
1"	1-1/2"	10,000	100	11988	11991	11992	11993
1-1/2"	1"	14,000	100	16765	18765	16683	49950
1-1/2"	1-1/2"	10,000	100	12002	12005	12006	12007
2"	1″	11,000	100	12016	12019	12020	12021
2"	1-1/2"	8,000	100	12023	12026	12027	12028
2"	2"	6,000	100	12030	12033	12034	12035
3″	3"	3,000	50	12051	12054	12055	12056

Ferrous

Non-Ferrous

Stainless

Exotic Alloys

Plastics

Composites







