

# SHUR-BRITE® Satin Finishing

## Disc Wheels

Due to the material profile running parallel to the work-piece, Mounted Disc Wheels are less aggressive than Flap Brushes, but produce a consistent satin finish. Disc Wheels are conformable and will not alter part geometry, ideal for removing light surface coatings or contaminants.

### Features

- ▶ Available in Heavy Duty and High Strength grades
- ▶ Conformable to contours and intricate parts
- ▶ Will not alter workpiece tolerances
- ▶ Portable, cushioned finishing and surface prep



## MOUNTED SATIN DISC WHEELS

Diameter	Width	Shank	Max RPM	Optimal RPM	Std. Pkg.	HD CRS	HS MED	HS FINE
1"	3/8"	1/8"	20,000	7,500	10	<b>46630</b>	<b>40433</b>	<b>40435</b>
1"	1/2"	1/8"	20,000	7,500	10	<b>46631</b>	<b>40434</b>	<b>40436</b>
1-1/2"	7/8"	1/8"	13,000	6,000	10	46632	<b>40437</b>	<b>40439</b>
1-1/2"	1"	1/8"	13,000	6,000	10	<b>46633</b>	<b>40438</b>	<b>40440</b>
2-3/8"	1/2"	1/4"	12,000	5,000	5	-	38182	38181
2-3/8"	1"	1/4"	12,000	5,000	5	-	<b>10459</b>	<b>10460</b>
2-3/8"	2"	1/4"	12,000	5,000	5	-	<b>10461</b>	<b>10462</b>
3"	1/2"	1/4"	8,000	4,000	5	-	<b>38178</b>	38179
3"	1"	1/4"	8,000	4,000	5	-	<b>10463</b>	<b>10464</b>
3"	2"	1/4"	8,000	4,000	5	-	<b>10465</b>	<b>10466</b>

● Ferrous ● Non-Ferrous ● Stainless ○ Exotic Alloys ● Plastics ○ Composites